



[promultis]

Tetra X Table

The Promultis Tetra X Table is a complete multi touch, collaborative interactive surface solution that integrates the latest touch screen technology into a table.



43" TO 65" INTERACTIVE AREA AVAILABLE



20 OR 100 TOUCH POINTS
WITH PROJECTED CAPACITIVE
TECHNOLOGY



32 TOUCH POINTS
WITH INFRA RED
TECHNOLOGY



OPTIONAL INTEGRATED PC
MULTIPLE SPECIFICATIONS AVAILABLE



SECURE PC COMPARTMENT
AND CABLE MANAGEMENT



HDMI CONNECTIVITY



4K UHD, BACK-LIT LED SCREEN



OBJECT RECOGNITION
READY OPTION



EASY
ACCESS ALL



FILM OPTIONS

- ANTI-BACTERIAL
- ANTI-GLARE
- ANTI-SCRATCH



3 YEAR ON-SITE WARRANTY





Note: Product design specifications including dimensions are subject to change without notice and may vary from those shown.



[promultis]

49" Tetra X Table

The Promultis Tetra X Table is a complete multi touch, collaborative interactive surface solution that integrates the latest touch screen technology into a table.





Note: Product design specifications including dimensions are subject to change without notice and may vary from those shown.



[promultis]

49" Tetra X Table

The Promultis Tetra X Table is a complete multi touch, collaborative interactive surface solution that integrates the latest touch screen technology into a table.





Note: Product design specifications including dimensions are subject to change without notice and may vary from those shown.



[promultis]

55" Tetra X Table

The Promultis Tetra X Table is a complete multi touch, collaborative interactive surface solution that integrates the latest touch screen technology into a table.





Note: Product design specifications including dimensions are subject to change without notice and may vary from those shown.



[promultis]

55" Tetra X Table

The Promultis Tetra X Table is a complete multi touch, collaborative interactive surface solution that integrates the latest touch screen technology into a table.





Note: Product design specifications including dimensions are subject to change without notice and may vary from those shown.



[promultis]

65" Tetra X Table

The Promultis Tetra X Table is a complete multi touch, collaborative interactive surface solution that integrates the latest touch screen technology into a table.





Note: Product design specifications including dimensions are subject to change without notice and may vary from those shown.



[promultis]

65" Tetra X Table

The Promultis Tetra X Table is a complete multi touch, collaborative interactive surface solution that integrates the latest touch screen technology into a table.



Note: Product design specifications including dimensions are subject to change without notice and may vary from those shown.

CHASSIS FEATURES	
Materials	Aluminium
Glass type	Toughened
Base unit	Cable Management and PC shelf
Base	Weighted
PANEL	
Interactive area	43" 49" 55" 65"
Panel resolution	4K UHD 3840 x 2160
Native resolution	3840 x 2160 60Hz
Brightness (nits)	450
Contrast ratio	1500 to 1
Response time	6ms
Aspect ratio	16x9
Viewing angle	178° / 178°
Pixel pitch	0.744 (mm)
LCD Illumination	Backlit LED
Speaker	10W x2
ENVIRONMENT	
Operating temperature	50°F to 104°F (10°C to 40°C)
Operating Humidity	10% to 80%, non-condensing
Storage Temperature	-4°F to 113°F (-20°C to 45°C)
Storage Humidity	5% to 95%, non-condensing
SHIPPED WITH	
Cables	Power USB HDMI
Remote control	Included
User manual	Included
WARRANTY	
3 year repair or replace warranty as standard	
Extended warranties and SLA's available at an additional cost	

INFRA RED TOUCH	
Touch Points	32
Touch sensitive to	Finger, Opaque object, Stylus
Sunlight Sensitivity	Can be used in direct sunlight
Interpolation	32,768x32,768
Response time	Repeated touch <6ms
Drift	None
Temperature	-20°C~60°C
Accuracy	±2mm
Interface	USB-2
Relative Humidity	10%~90%RH
Supported	OS Windows, MAC, Linux, Android
PROJECTED CAPACITIVE	
Detection method	Projected Capacitive
Input method	Finger and gloved finger
Number of simultaneous touches	20 & 100
Noise Shielding	DISPLAX XTR-Shield™ Plus, a proprietary noise filtering technology
Aspect ratio	16:9
Controller	Printed circuit board with mini USB connector
Adhesive	Permanent
Interface	HID
OS with multitouch	Windows 8.1, 8, 7, 10; Ubuntu 12.04; Android; Chrome OS
OS with single touch	Mac OS X Yosemite
OS with mouse emulation	Spinetix Media Player HMP 200
Data connectivity	USB 2.0
Touch accuracy	1mm absolute

PERFORMANCE	
Substrate thickness	Up to 6mm
Touch response	5 milliseconds
Calibration	Available using control panel: no drift
POWER CONSUMPTION	
Average power consumption (P)	USB powered @ 5V
	Peak consumption: 410 mA
	Operation consumption: 370mA
RELIABILITY	
Operating temperature range	-20°C to 70°C
Operating humidity range	0% to 96%
WEIGHT	
Gross Weight (50") (Approx, KG)	75



Note: Product design specifications including dimensions are subject to change without notice and may vary from those shown.