

# Promultis Totem DUO

The Promultis Totem DUO is a versatile dual-sided display offering both infrared (IR) and PCAP touch options, perfect for interactive digital signage and customer engagement.



Note: Product design specifications including dimensions are subject to change without notice and may vary from those shown. Please call us for the most up to date specifications and dimensions.



[promultis]



For more exciting multitouch products visit  
[www.promultis.info](http://www.promultis.info)  
or call +44 (0) 239 251 2794

# 55" IR Touch

SPECIFICATIONS	
Panel Size	55" TFT-LCD
Display Area (mm)	(W) 1209.6 x 680.4 (H)
Aspect Ratio	16:9
Maximum Resolution	1920 x 1080
Display Colour	16.7M
Pixel Pitch (mm)	(H) 0.63 x 0.63 (V)
Brightness (nits)	450 cd/m <sup>2</sup>
Contrast	3000:1
Visual Angle	178°/178°
Response Time	5ms
Life (hrs)	>60,000 (hrs)
INPUT & OUTPUT	
HDMI	1
USB	1
VGA	1
Audio	1
Lan	1
Speaker	2x5W (9Ω)
VIDEO	
Colour System	PAL/NTEC/SECAM
SCREEN MENU DISPLAY	

Note: Product design specifications including dimensions are subject to change without notice and may vary from those shown. Please call us for the most up to date specifications and dimensions.



[promultis]



For more exciting multitouch products visit  
[www.promultis.info](http://www.promultis.info)  
or call +44 (0) 239 251 2794

# 55" IR Touch

Menu Language	English
<b>POWER</b>	
Power Supply	AC100~240V 50/60Hz
Maximum Power Consumption	≤380W
Standby Power Consumption	<5W
<b>DETAILED FUNCTIONS</b>	
Video Format	MPEG1/MPEG2/MPEG4/DivX/ASP/WMV/AVI
Audio Format	Wave/MP3/WMA/AAC
Image Format	JPEG/BMP/TIFF/PNG/GIF
Image Resolution	480p/720p/1080p
<b>TEMPERATURE</b>	
Working Temperature	0°C~50°C
Storage Temperature	-20°C~60°C
Working Humidity	85%
Storage Humidity	85%
<b>APPEARANCE</b>	
Colour/ Appearance	White/Black/Customised
Case	Metal Case SPCC
Installation	Floor-Standing
Certificate	CE FFC
Quality Standard	ISO9001, CCC
<b>TOUCH PANEL</b>	

Note: Product design specifications including dimensions are subject to change without notice and may vary from those shown. Please call us for the most up to date specifications and dimensions.



[promultis]



For more exciting multitouch products visit  
[www.promultis.info](http://www.promultis.info)  
 or call +44 (0) 239 251 2794

# 55" IR Touch

Specification	Infrared Touch
Accuracy	± 2mms
Transmittance	≥92%
Hardness	7H
Click Manner	10 Points
Response Time	≤10ms
Life Time	More Than 600,000,000 Times
COMPUTER SPECIFICATIONS	
Main Chipset	NM70M-I7M2
CPU	I7-3520M 2.9GHz-3.6GHz
System Bus Frequency	800/1066/1333MHz
Graphics Card	Integrated
Audio Card	Integrated AC97
Network Card	Integrated 10/100/1000M Adaptive
Memory	4G DDRIII
Hard Disk	128G SSD
Wi-Fi	Included
OS	Windows Trial Version

Note: Product design specifications including dimensions are subject to change without notice and may vary from those shown. Please call us for the most up to date specifications and dimensions.



[promultis]



For more exciting multitouch products visit  
[www.promultis.info](http://www.promultis.info)  
or call +44 (0) 239 251 2794

# 55" PCAP Touch

SPECIFICATIONS	
Panel Size	55" TFT-LCD
Display Area (mm)/mode	1209.6 (W) x 680.4 (H) 16:9
Maximum Resolution	3840x2160
Display Colour	16.7M
Pixel Pitch (mm)	0.63 (H) x 0.63 (V)
Brightness (nits)	450cd/m <sup>2</sup>
Contrast	3000:1
Visual Angle	178°/178°
Response Time	5ms
Life (hrs)	>60,000 (hrs)
INPUT & OUTPUT	
HDMI	2
USB	2
Audio	2
LAN	2
Wi-Fi Antenna	2
Speaker	2x5W (9Ω)
VIDEO	
Colour System	PAL/NTSC/SECAM
SCREEN MENU DISPLAY	
Menu Language	Any/English

Note: Product design specifications including dimensions are subject to change without notice and may vary from those shown. Please call us for the most up to date specifications and dimensions.



[promultis]



For more exciting multitouch products visit  
[www.promultis.info](http://www.promultis.info)  
or call +44 (0) 239 251 2794

# 55" PCAP Touch

POWER	
Power Supply	AC100~240V 50/60Hz
Maximum Power Consumption	≤380W
Standby Power Consumption	<5W
TEMPERATURE	
Working Temperature	0°C~50°C
Storage Temperature	-20°C~60°C
Working Humidity	85%
Storage Humidity	85%
APPEARANCE	
Colour/Appearance	White/Black/Customised
Case	Metal Case SPCC
Installation	Floor-Standing
Certificate	CE FCC
Quality Standard	ISO9001, CCC
TOUCH PANEL	
Specification	PCAP Touch
Accuracy	±2mms
Transmittance	≥92%
Hardness	7H
Click Manner	10 points
Response Time	≤10ms

Note: Product design specifications including dimensions are subject to change without notice and may vary from those shown. Please call us for the most up to date specifications and dimensions.



[promultis]



For more exciting multitouch products visit  
[www.promultis.info](http://www.promultis.info)  
or call +44 (0) 239 251 2794

# 55" PCAP Touch

Life Time	More Than 600 million times
DETAILED FUNCTIONS	
Video Format	MPEG1/MPEG2/MPEG4/DivX/ASP/WMV/AVI
Audio Format	Wave/MP3/WMA/AAC
Image Format	JPEG/BMP/TIFF/PNG/GIF
Image Resolution	480P/720P/1080P/2160P

Note: Product design specifications including dimensions are subject to change without notice and may vary from those shown. Please call us for the most up to date specifications and dimensions.




[promultis]



For more exciting multitouch products visit  
[www.promultis.info](http://www.promultis.info)  
or call +44 (0) 239 251 2794

# 55" IR Touch



Note: Product design specifications including dimensions are subject to change without notice and may vary from those shown. Please call us for the most up to date specifications and dimensions.




[promultis]



For more exciting multitouch products visit  
[www.promultis.info](http://www.promultis.info)  
or call +44 (0) 239 251 2794



# 55" PCAP Touch



Note: Product design specifications including dimensions are subject to change without notice and may vary from those shown. Please call us for the most up to date specifications and dimensions.



[promultis]



For more exciting multitouch products visit  
[www.promultis.info](http://www.promultis.info)  
or call +44 (0) 239 251 2794